

FMX 410 hp, 6x2 rigid		Trucknor Haugesund AS JBR2013000011 Trucknor Hordaland AS Laxo Mekan AB / Sweden	
FO Number / OM Number		Print date	
890-32-9445 / 13209445		2024-06-03	
Chassis Number	VIN Number		
A-762709	YV2XZ22C9EA762709		
Build week	Confirmed delivery day	Planned arrival date	
201408	2014095 (YYYYWWD)		
Latest update			
2015-04-08 (YYYY-MM-DD)			
Chassis Unique Homologation Document		General Homologation Document	
State Certo		Volvo Powertrain RMI statement Volvo Truck RMI statement COP Statement	
		Supplementary drawing(s): - POWER TAKE-OFF 22072271_02.dxf.zip 22072271_02.pdf - REAR FENDER 3200301.dxf 3200301.pdf - BODY ATTACHMENT 3200308.dxf.zip 3200308.pdf - SUP 3200310.dxf.zip 3200310.pdf - AD-BLUE TANK 3200344.dxf.zip 3200344_2.pdf - CAB-DAY Classic 3200351[1].zip 3200351.pdf - EXHAUST SYSTEM 3200372.dxf.zip 3200372.pdf - SUP 3200383.dxf.zip 3200383.pdf - FMX Attachment points - Front mounted equipment FMX_Version4.zip FMX_Version4_withFLS.jpg	
BEP, chassis unique drawing in scale No general chassis drawing found! Data Sheet : fm62tr1hax_nor_nor.pdf			
Tyres front		Tyres rear	
385/65 R22.5 CONTINENTAL HSW2 SCAN		295/80R22.5 CONTINENTAL HDW2 SCAN 385/65 R22.5 CONTINENTAL HSW2 SCAN	

Technical Specification

		Administration
Variant	Description	
USWAPACK	Without swap body	
BC-FMX	FMX model	
FMX62R41	FMX 410 hp, 6x2 rigid	
NOREG003	Region 3 NOR	
VISIX	Visibility package FMX	
MEDHYS	Medium-high chassis, rear air suspension and hydraulically steered tag axle with single wheels	
EUDRPA1	EUD ADJUSTMENT VARIANT (ONLY ENG-VE13)	
EUDPAD13	DNP ADJUSTMENT EURO4 D13 BLOCK 637	
EPAM362	EUD ADJUSTM FM13 62	
EUDPEU5M	DNP ADJUSTMENT EURO V MANDATORY	
EUFMXRPA	EUD FMX PRICE ADJUSTMENT	
ULSA	Without local sourcing	
USWUR	REMOTE SOFTWARE UPGRADE DISABLED	
DF-FAM	DYNAFLEET FUEL ADVICE MONTHLY SUBSCRIPTION	
UDRUT	Without My Truck service/app	
TC-DISTR	Distribution transport cycle (driving_pattern)	
MFACTSE1	MAIN FACTORY SWEDEN	
EU6SCR	Euro 6 with SCR, particulate filter and EGR, Turbo-S	
UPEPROT	WITHOUT PERSONAL PROTECTION PACKAGE	
DF-FUELM	Fuel & Environment in Volvo Connect, recurring subscription	
DF-DTMM	Driver Times in Volvo Connect, monthly subscription	
DF-POSM	Positioning in Volvo Connect, recurring subscription	
DF-MSGM	Messaging in Volvo Connect, recurring subscription	
NOR	Norway	
WB3900	Wheelbase 3900 mm	
STG-LR	STEERING GEAR LEGAL REGULATIONS	
FFL1275	Front frame length 1275 mm	
24-HDV	New generation Volvo heavy vehicle	
FM 62 TR	FM 6x2 tag, rigid	
DIRT-MED	Between 10-40% of the driven distance on roads/surfaces defined as "dirty"	
EGR-H	Exhaust gas recirculation, hot	
TYPE-FM	FM Low tilt cab	
UWVTAPPR	Not whole vehicle type approved for EC	

6*2	6x2 - Three axles, one rear axle driving
RIGID	Rigid model
RC-SMOOT	Smooth road conditions (at least 95% driving on surfaced roads)
GCW60.0	Gross combination weight 60.0 tonnes
ENG-VE11	10.8-litre six-cylinder engine
VH4.2	Total vehicle height max. 4.2 metres
RAL19	Rear axles load 19 tonnes
STWPOS-L	Left-hand drive
VW2600	Vehicle width 2600 mm
FAL9.0	Front axle load 9.0 tonnes
UADR	Without ADR adaptation (transportation of dangerous goods)
MA-BAS	Basic market adaptation
CHH-MED	Chassis height medium - approx. 900 mm above ground level
COG-BAS	Complete superstructure & payload centre of gravity 0.5-1.0 m above top of truck frame
CURV-L	Low curve density (the speed is seldom reduced due to driving in curves)
VUPT-A2	VEHICLE UPTIME ENABLED. AUTOMAT SERVICE ACTIVATION SETTING 2
NOR-PRO	PRE PROFORMA NORWAY
NR-80EC	EC external noise requirement 80 dB(A)
UADRC	Without ADR classification
B-SKIPL	Skip loader
ULHE1	Without tail lift
ULHE2	Without crane
ULHE3	Without snow plough
ULHE4	Without miscellaneous load handling equipment
T-PFLAT	Predominantly flat operating topography
VASSIS2	Vehicle assistance service enabled, with voice channel
RFUEL	FICTIOUS VARIANT RIGHTHAND FUELTANK (ALL SIZES)
UWVTA	Not Whole Vehicle Type Approved
RT-STEEL	Steel rims on all axles
F385-65A	Front axle tyre 385/65R22.5, tubeless
D295-80A	Driving axle tyre 295/80R22.5, tubeless
TA-HYSBS	Electro-hydraulically steered single-wheel tag axle with steering lockout at 38 km/h
T385-65A	Tag axle tyre 385/65R22.5, tubeless
UPHTRI13	LEATHER, ROBUST TRIM VINYL
UOFFROAP	Without construction package
UMBAC	Without market business package
ESH-REAR	Horizontal silencer, rear exhaust outlet
FMX-DAY	DAY CAB FMX
URESTING	Without Living package
AUDHIG	HIGH LEVEL SOUND SYSTEM
UL-FUEL	Without left side fuel tank
R405A71	Right 405-litre, D-shaped aluminium fuel tank, 710 mm high
MIRCOMFX	Robust rear-view and wide-angle mirrors (both sides), kerb observation mirror
DRIVEFM+	Driving plus package FM
1DAYDIG	One-day digital tachograph, EC approved
NOR-MSP	Norway

ENGINE WITH MOUNTING AND EQUIPMENT

Variant	Description
FTCL-BAS	Fuel tank with basic ground clearance
EAP-LHD2	Light heavy duty engine application (std pistons and corrosion resistant valve seats)
UFTI	Without fuel tanks interconnection
OILS-PL	Plastic oil sump
TURB-B	Basic turbo
HS-BAS	Muffler heat shield (EATS), basic
CCV-OX	Open extended crankcase ventilation with oil separator and maintenance-free gas centrifuge
ADTP-R	AdBlue tank on right hand side
UADTC	Without AdBlue filler cap
OBDEC1	High emission level consequences
OBDEP-B	EU6 mandatory on board diagnostics, phase B regulations
AF-R	Hot fuel recirculation heated fuel filter
ULFUEL	Without left side fuel tank
RFUEL405	Right fuel tank 405 litres
USPEEDDU	Without dual speed limiter
SPEED90	Road speed limiter setting 90 km/h
CRUISEC	Basic cruise control with controls in steering wheel
AIRIN-HI	High air inlet
ENGPROT	Engine protection
FUELTS71	Semi rectangular 710 mm diam fuel tank
TNK-SING	Single mounted fuel tank
FTANK-AL	Aluminium fuel tank
FCAP-UL	Non-lockable diesel and AdBlue filler caps
STRAP-P	Painted fuel tank straps
UEXST	Without vertical exhaust pipe
EXD-REAR	Exhaust direction, rear

UEXSH	Without extra exhaust heat shield
EAS-SD	Selective Catalyst Reduction + Diesel Particulate Filter, ceramic
EM-EU6	Emission level Euro 6
ACL1ST	Air cleaner with one filter element
PRIM-MAN	Manual priming pump for removal of air in the fuel system
USPLIMS	Without speed limiter sensor
SCRS-EHH	Electrically heated SCR system equipment
EASO-H	Horizontal orientation of the aftertreatment system
UTFUEL	Without temporary diesel tank
ADB064	AdBlue tank: usable volume 64 litres, 710 mm high, mounted on chassis side
FUEFE2LW	Large engine-mounted dual fuel filter with water separator and drain
UXFUEL	Without extra fuel filling
ATL40	Ambient temperature down to -40 °C, colder allowed up to 25 h/year
ATU40	Ambient temperature up to +40 °C, warmer allowed up to 25 h/year
FUFF-AS	Fuel filling anti-spillage device
UFUEQWH	Without fuel line heater
EAB-NO	Engine application band, normal
TURBO-S	Turbo single stage
BUGNET	Insect screen (PVC-coated fibreglass) in front of radiator
D11K410	410 HP
ETOR1980	Engine torque range 1911 - 1980 Nm
EBR-VEB	Volvo Engine Brake, VEB (compression brake with exhaust pressure governor, EPG)
UWILDBAR	Without wild bar

ELECTRIC POWER SUPPLY, LIGHTING, INSTRUMENTS

Variant	Description
ASSIST4	Assistance switch and microphone, Volvo Action Service
UHWSS	Without forward collision warning
ARLIG-PK	Additional rear light preparation kit with two 2.5 m wires with 7 pole DIN connectors
RSSENS-W	Wipers rain sensor
TAS-DIG	One-day digital tachograph, EC approved (annex 1B regulation)
INLI-BAS	Interior white light with smooth light transition at on/off, no dimming
URESTS	Without reflective white stripes on chassis side
UALCOLOC	Without alcolock
URPLCR	Without rear position lamp
BBOX-L	Battery box on left-hand side
2BATT225	Batteries, 2x225 Ah
24V	Electrical system 24V
UDAS	Without Driver Alert Support
PHONE-PK	TELEPHONE PREPARATION KIT
HL-ASYMR	Headlamp asymmetry setting for right-hand traffic
DETECT-S	Smoke detector in cab
HORN-ELS	Single electrical front horn
HORN-F1S	Single-tone Jericho horn behind grille, operated by steering wheel buttons
URTOLL	Without electronic road fee equipment
USOUTLET	Without electrical outlet in sleeper compartment
UFMS	Without fleet management system gateway
TWEETER	Tweeter
ECBB-HIG	Body builder electrical centre, body builder module with 14 high and 4 low digital outlets
POSLMP-W	White position lamps on front roof corners
UASL	Without spot lamps in sign box
WWF-ALC	Windscreen washer fluid with alcohol additive
WL-CHPK	Preparation kit for work lamp (switch with cable to frame, by gearbox)
BEACOA2F	Two amber LED beacons on cab front roof
SPG-KM	Speedometer scale: km/h
EST-AID	Engine intake air heater
TL-BAS	Basic tail lights with bulbs
MSWI-C	Main switch on chassis
UFOGLAMP	Without front fog lamps
UDRIVL	Without extra main beam
UAUXL	Without preparation kit for snow plough lamp
UHLADJ	Non-adjustable headlamp beam
HL-CLEAN	High-pressure headlamp cleaner
IMMOBIL	Immobiliser
IDLAMP-W	Three white identification lamps on mid front roof
MARKL-SR	Side and rear marker lamps
SRWL-2RW	2 white LED reverse/work lamps, rear-facing on rear chassis, 3-pos switch (On/Off/Reverse auto On)
DIFL-SWE	Driver information primary language Swedish
DISL-DEU	Driver information secondary language German
KEYB-SWE	Swedish keyboard
USAS	Without Service Alert System
HL-BHID2	HEADLAMPS, BI-XENON, HIGH INTENSITY DISCHARGE, HEAVY DUTY
TEMP-TRA	Transmission lubricant temperature gauge
24AL110B	Alternator 110 Ampere
SI-GRAF	Speedometer instrument, tachograph

1DAY-STD	1 day tachograph, EC
CALI-DIG	Digital calibration of tacho. & speedometer
UAMPL	Without external amplifier
UCLSTAT	Without static cornering lights
UBAMAFRE	Without enhanced flooded batteries
BEPR-T2	Bodywork electrical and software preparation for tipper with remote control
WLC-H2W	2 white LED work lamps, high-mounted on back of cab (switch included)
TD-LED	TD-LED detects trailers that have either bulb lights or LED lights.
BBCHAS3	Three 7-pole bodywork connectors on chassis
TLB-BAS	Basic tail light brackets
UANTCB	Without preparation kit for communication/CB radio
SPK-DADO	Loudspeakers in dashboard and doors
AIP-BT	Audio integrated handsfree bluetooth phone
ACON-USB	USB audio communication connector
XCON-AUD	Audio AUX Line in connector
AESW2	2 bistable bodywork switches (marked AUX1/AUX2)
TGW-3GWL	Telematics gateway with 3G modem and WLAN
UHLPPRO	Without headlamp protectors
REMC-MF	Wireless remote control, multi-functional
BUPALARM	Reversing warning
UARL	Without flexible reading lamps
UINFOT	Without TV mounting preparation kit
TESP-T	Driver Service Platform
BUPMON	Reversing camera
ULSS	Without lane keeping features
ULCS	Without Side Collision Avoidance Support
UARSL	Without additional road speed limiter control
AUDWB1	Audio wavebands FM 87.5-108.0 MHZ, AM 522-1611 KHZ
BULBKIT	Bulb and fuse kit
UEIDLESD	Without engine idle shutdown
ULAMPIN	Without inspection lamp
SPOTP-RF	Preparation kit for spot lamp in cab roof and front, max 280 W
LOADIND	Load indicator, shown in instrument display and side display
UALARMB	Without anti-theft alarm
AUXSW-4	Hardwiring for 4 extra switches (from body builder electrical centre to instrument panel)
INST-MED	Medium level instrument cluster - 4 inch colour display 240x320 pix
AUD-CDM	Radio with CD player, MP3 capability
BATTIND	Battery voltmeter, ammeter and battery status gauge with visual alerts
DRL-LED	Daytime running lamps (LED)
SID-HIGH	9" colour side display
EWT3900	Equivalent wheelbase turning, 3900 mm
BLIGHT-B	Basic brake light

POWER TRANSMISSION

Variant	Description
TRAP-BAS	Basic gearbox range housing
APF-BAS	I-Shift with basic PTO functions
RSS1360	Rear single reduction solo axle - axle load 13 tonnes, GCW 60 tonnes
CS43B-O	Single-plate clutch, plate diameter 430 mm
TRA-AMT	Automated mechanical gearbox
GSS-AGS	I-Shift, gear shift lever on seat
AT2612E	I-Shift automated mechanical 12-speed gearbox without clutch pedal, 2600 Nm, GCW 60000 kg
TRAN-V	Volvo powertain gearbox
PTER-DIN	Rear engine, clutch-ind. PTO, splined shaft groove (fem), close-coupled pump DIN 5462/ISO7653
TC-MWO	Basic performance cooler for manual/I-Shift gearboxes - water/oil
PTOENG-R	Rear engine mounted PTO
UPTOTR	Without gearbox PTO
RAT3.40	Rear axle ratio 3.40
PROPS-M	Propeller shaft dimension medium, single joint
DL-FULL	Differential lock between axles and wheels
EPTT650	Engine PTO maximum torque 650 Nm
UTPTT	Without gearbox PTO torque
UPTOTRA	Without PTO transmission
AMSO-AUT	I-Shift manual gear shifting available in automatic mode, including kick-down function
AVO-BAS	I-Shift with basic application software
TP-DICON	I-shift Distribution and Construction optimized gear changing software
SRED-V	Single reduction rear axle

BRAKE

Variant	Description
UCLUAIRC	Air compressor without clutch
PBREL-A	Automatic parking brake release
UTECABLE	Without electrical cable for trailer brake
UTBCONN	Without trailer brake connection
TREL-PK	Trailer electrical preparation kit (chassis/cab wiring)
UPNPROT	Without protective cover for chassis-mounted pneumatic equipment

UTBHOSE	Without trailer brake hoses & cables
EBS-MED	EBS (Electronic Braking System), Medium package
UTRBSTRE	Without trailer stretch brake
PDC-OFF	Pneumatic distribution centre outside frame, front
UPBR	Without pusher brake
UPBRAD	Without pusher axle disc brake dimension
UTRACON	Without converter for trailer lights
UTABS	Without trailer ABS circuit converter
ATANK-ST	Steel air tanks
BF-DIBAS	Disc brakes with solid discs
BR-DIBAS	Rear brake disc, solid
FBRA-D43	Front axle disc brake diameter 410 mm
BT-DIBAS	Brake disc trailing, solid
RBRA-D43	Driving axle disc brake diameter 430 mm
TBRA-D41	Tag axle disc brake diameter 410 mm
BSYS-EBS	Electronic brake system
DBRDUST	Dust shield for rear brakes
UAUXPARK	Without extra parking brake
BRAKE-DV	Disc brakes
ATNK-GEN	Air tank capacity, standard
UATNKRUB	Without air tanks with rubber rings
FBREG-E	Front axle regulating brake valve for EBS
SIL-BRV	Brake valves silencer
URETARD	Without gearbox-mounted retarder
UAUXATNK	Without extra air tank
2COM1100	Dual-cylinder air compressor 760 cc, 1100 l/min
TRBRAKE	Trailer brake valve
UTCP	Without trailer connection bracket position
TRBR-STA	Stationary trailer brake check
ABS	Lock free brakes
ESP-BAS1	ESP for tractor combinations with ABS/EBS or rigid vehicles/combinations with std center of gravity

WHEEL SUSPENSION AND STEERING

Variant	Description
PSP-VAR	Power steering pump with variable displacement
STW-D450	Steering wheel diameter 450 mm
U1PAC	Without pusher axle capacity
1TAC75	Tag axle capacity 7.5 tonnes
STWM-BAS	Steering wheel material basic
FAT-RIG	Conventional front axle suspension
TA-HYDRS	Hydraulic steered tag axle
RADT-GR	Rear air suspension - two axles, one pusher, one tag
FA-LOW	Front axle low ground clearance with high offset
FAA10	One front axle, non-driving
RSTS-EHY	Rear steering system, el. hydraulic
ACTST-TQ	Volvo Dynamic Steering
BL-BAS	Basic bogie load distribution
UAUXPSP	Without extra power steering pump
URVCERT	Without vehicle certification, road
UBCYLPRO	Without brake cylinder protection
STG23.2	Steering gear ratio 23.2
PSS-SING	Single power steering system
STGW-ADJ	Manually adjustable steering wheel
ULDFA	Without load distribution on front axles
RALIM20	First rear drive axle load limiter, 20 tonnes
LIFT-BAS	Bogie lift for non-driven rear axle

FRAME, SPRINGS, DAMPING AND WHEELS

Variant	Description
FSS-AIR	Front air suspension
RSS-AIR	Rear air suspension
FSTAB2	Front anti-roll bar, high stiffness
SUP-BAS	Standard side underrun protection, aluminium
RSTAB2	Rear anti-roll bar, high stiffness
FIL-EEEE	Frame inner liner from end of engine to end of frame
SUSPL-EC	Remote control for air suspension levelling
WPRING-P	Painted wheel protection ring
WTDF22.5	Front wheel and tyre inner diameter 22.5 inches
WTDD22.5	Driving wheel and tyre inner diameter 22.5 inches
WTD22.5	Tag wheel and tyre inner diameter 22.5 inches
WTT-D335	Tag disc wheel, 335 mm
WTT-SING	Single wheel and tyre mounting on tag axle
WMF-ST	Front steel rims
WMD-ST	Drive steel rims
WMT-ST	Tag steel rims
WDF1175	11.75" front axle rims

WDD900	9.00" driving axle rims
WDT1175	11.75" tag axle rims
UINFLAHO	Without tyre inflation hose
UTIREPM	Without tyre pressure monitoring
TD295-80	Driving axle tyre dimension 295/80
TMF-CONT	Continental front axle tyre
TMD-CONT	Continental drive axle tyre
TMT-CONT	Continental tag axle tyre
TR-EUR	Tyre region Europe
ASF-DL3	Air suspension with three ride heights
UGUARD	Without guard plate for cooling pipes and oil sump
USPWCAT	Without spare wheel carrier
USPWCARR	Without spare wheel carrier
USPWT	Without spare wheel
UTFSEAL	Not sealed front tyres - no run flat protection
UTDSEAL	Not sealed drive tyres - no run flat protection
UTTSEAL	Not sealed trailing tyres - no run flat protection
FSI-REAC	Front air suspension with reaction rod
UGAUGETP	Without tyre pressure gauge
UDECALTP	Without tyre pressure decal
URUPP	Without rear underrun protection pos.
ACMR1	One extra crossmember in rear overhang
WTA-TL	tubeless tyres
WSTUD-S	Short wheel studs (for steel rims or aluminium rims with dual holes)
UTPSEAL	Not sealed pusher tyres - no run flat protection
UTMPR	Without pusher axle tyre
RSLS-BAS	Basic levelling stroke in rear air suspension (high ground clearance under rear axle member)
XMBRR-B	Basic rear crossmember closing
WTD-DUAL	Dual mounting of drive axle wheel and tyre
UMRUP	Without rear underrun protection
FSM-MF	Maintenance-free front suspension
UWCAP	Without wheel caps
USUPS	Without footstep in side underrun protection
UPTT	Without pusher axle tyre tread
FUP	Front underrun protection
UWTDP	Without wheel and tyre diameter on pusher axle
UFRF	Without frame rail clearance
RSAP-BAS	Standard rear suspension application (without reinforcements)
UWTPM	Without wheel & tire mount pusher axle
UFALIM	Without front axle load limiter
UFAS	Without front axle spread
UTWP	Without pusher axle wheel type
UWDP	Without pusher axle wheel dimension
URESTRUP	Without reflective red stripe on rear underrun protection
UFRACLOS	Without frame end closing
TXMB4827	Transmission crossmember web location (main 4827)
RFEC-S	Rear frame end, straight cut (for regular platform applications)
XMBT-S	Strong transmission crossmember
FST8080	Frame thickness - web 8.0 mm / flange 8.0 mm
FRAME300	Frame rail section external height 300 mm
RFL2695	Rear frame length 2695 mm from 1st driving axle
URUP	Without rear underrun protection
FST-AIR	Front air suspension
RST-AIR4	Rear air springs (extra stiff)

BODY, CAB AND INTERIOR

Variant	Description
UEBHEAT	Without electrical engine block heater
FMUDE-TW	Front mudguard extension, tyre-width dependent
UCSPL	Without storage in lower centre instrument panel
ARU-BAS	Vinyl armrest upholstery
GRABHI-B	Instep grab handle, basic
USEATV	Without ventilated seat
UBUMPSP	Without front bumper spoiler
UTBL	Without toolbox on the left hand side
UTBR	Without right toolbox
USBPREDS	Without driver's seat belt pretensioner
JACK-12T	Hydraulic jack, 12 tonnes, height 180-315 mm, weight 7.0 kg
TOOLKIT	Extended tool kit in storage compartment behind left seat
URUSTP	Without transport rust protection
WARR300	Warranty booklet, 300 000 km
DGLAS-H	Tempered door window glass
UCOFMAK	Without coffee maker
USTUC	Without extra storage compartment under cab
UWRNLAMP	Without portable warning lamp

USBPREPS	Without passenger seat belt pretensioner
7107WHIT	Cab colour solid clear coat Traffic White (NCS 0502-G27Y)
PAICS-B	PAINTING LEVEL BASIC
ULADDER	Without ladder on back of cab
EMBL-MO	Emblems mounted
BOTH-D	One bottle holder under dashboard centre section
UMICROWV	Without microwave oven
SUPH-L1	SEAT UPHOLSTERY, LEATHER VERSION 1
SEATBRIA	Seat belt reminder in instrument, with audio
UTABLE	Without foldable table
CABPT-R2	Two front cab roof pass-throughs, one on each side
WARNVEST	Reflective vest, fulfils European standard EN 471 class 2
UAIRBAG	Without airbag
URUS	Without storage in rear upper cab
UOLMAT	Without overlay mattress protector
TELECARD	Volvo Action Service Europe
WRITEPAD	Writing pad with paper clamp
USIGNS	Without green Euro emission level sign
URLS	Without storage under bunk
UVANMIR	Without vanity mirror
DIMPLATE	Dimension plate according to directive 96/53/EEC (dimensions and coupling distances)
UMATTRES	Without lower bed mattress
DLAY-BAS	Basic dashboard layout, any flexible body builder switches placed in centre
DTRI-RAV	Dashboards, door panels and steering wheel Raven (dark grey)
UCFAFS	Without retractable extra footstep in cab front bumper
HCC-EXT	Unlockable front lid - Exterior hood catch control
SBD-BAS	Black safety belts, passenger and driver seats
SBP-BAS	Black safety belt, passenger seat
UADH	Without roof aerodynamic device height
UCPARKC	Without electric parking cooler
UADCF	Without aerodynamic flaps on chassis fairings
AIDKIT	First aid kit
ISUNF-MD	Interior front sun visor with mirror on driver side
UAUXFS	Without extra footstep in cab side
SIMC1	Sim card, Telenor SE
CSPT-T	Center section dashpanel top, tray
DS-AS	Driver seat air supply
UPUBS	Without additional printed Driver Guide
EXTL-BAS	Exterior trim level basic
UTBUNK	Without top bunk
UIDLMPSW	Without switch for identification lamps
CSPU-S	CENTER SECTION DASH PANEL UPPER STORAGE
UAWINDR	Without window in back of cab
ROHO-MAN	Manually operated roof hatch UPDATED
UCABSIGN	No sign box decal. With (or prepared for) illumination: white area. No illumination: black area.
UEMIEMBL	Without emission level emblems
CAB-DAY	Day cab
RCABS-M	Mechanical rear cab suspension
CTILTP-M	Manual cab tilt pump
UADFS	Without extra DIN slots in front shelf (blind slots)
FMUD-AS	Mudflaps with spray suppression on all front-axle mudguards
USIDESTP	Without side footstep, ladder or handle
FCABS-M	Mechanical front cab suspension
UCURTAIN	Without curtains
UAWINDS	Without rear side window
WLIFT-EB	Electrical window lift
RHATCH	Roof hatch
GLAS-TIN	Tinted windows
ULBK	Without lower bed
FMAT-RU2	FLOOR MAT, RUBBER, EXTENDED SIDE
PST-STD2	Passenger seat Regular, non-suspended
CABH165	Cab height 165 cm
ACCB-R-F	Accessory bracket mounted on front roof
CABL165	Cab length 165 cm
UREFS	Without reflecting stripes on cab
LANG-DN	Danish/Norwegian text on decals/signs
PUBL-NOR	Printed Driver Guide in Norwegian
CERT-EC	Certification labels for EC countries (except DEU/FRA/GBR)
LOCK-REM	Central door locks with remote control
REFL-EC	Reflectors (ECE70 & TSVFS 1991:45)
DPAN-B2	BASIC DOOR PANEL 2, (FLEET SPEC)
UMATINS	Without insert mat on engine tunnel
MIR-ELOP	Electrically heated and operated external rear view mirrors on both sides
AMIR-WB	Wide angle mirror on both sides

AMIR-F20	Front close-view mirror above windscreen, passenger side (radius 200 mm)
TRIM-RB	Vinyl interior trim in matching grey nuances
ARMRE-DB	Two armrests on driver's seat
UROSIL	Without roof sign illumination
DST-CF5	Driver's seat Comfort, belt in seat, heated, adjustable lumbar&side support, extendable seat cushion
FIREXT3N	Fire extinguisher 3 kg, Norwegian decal
UPARKH	Without parking heater
AMIR-S30	Close view mirror on passenger side, radius 300 mm
ISUNS-DS	Side interior roller blind on driver's side, manually manoeuvred
UAS	Without extra shelves in front upper storage compartments
CU-ECC	Automatic climate control with sun sensor
BUMP-HD	Heavy-duty front bumper
TOWF-HD1	One heavy-duty front towing device
UWINREP	Without cab side window replica
UBEDNET	Without net for lower bunk
USAFETYB	Without safety box
MPLA-ENG	Manufacturing plate, English version
USLCP	Without sleeper control panel
SUNV-H	Exterior front sun visor, transparent dark-grey
UADROOF	Without roof air deflector
AD-SIDES	Cab side air deflectors, short
UADCHAS	Without chassis fairings
WARNTRI2	Two warning triangles
UMIRRTXT	Without mirror warning text
ETSB-FRS	Storage at front of engine tunnel and immersed in RH side of tunnel
UREFRIG	Without refrigerator or preparation kit for refrigerator
USIGN	Without low-noise L-sign in front
XINS-CAB	Extra thermal cab insulation, rear and side walls
UGUARDW	Without windscreen stone guard
Miscellaneous	
Variant	Description
UFFEND	Without mudguards on second front axle
URFCAR	Without rear mudguard carrier
RMUDF-AS	Mudflaps with spray suppression on all rear-axle mudguards
RFEND-B	Rear 3-piece mudguards (anti-spray) on all rear axles
UFWPOS	Without king pin position
U5WMOUNT	Without fifth wheel mounting
U5WHEIG	Without fifth wheel leg height
UKPSIZE	Without king pin size
U5WTYPE	Without fifth wheel
URAMP	Without fifth wheel ramp
UTOWTYPE	Without towing member
UTOWMBR	Without towing member
UCOUPLIN	Without towing coupling
UTOWR	Without rear towing device
UWHCHOCK	Without wheel chocks
URDECK	Without deck plates
UTAIL	Without tail lift preparation kit
UHPG	Without gearbox-mounted hydraulic pump
UFFTP	Without second front axle fender top height
UNIFORM	Basic platform vehicle
ULCHF	Without load carrier
ULCL	Without load carrier length
RFC-1	Mudguard installation according to Spray suppression, EC on-road requirements
RFH-BAS	Basic mudguard installation height on 2nd front axle and rear axles
U5WLM	Without fifth wheel maintenance
FACT-SE1	Final assembly plant Sweden
10500MM	Frame length 10500 mm
UCHAINS	Without snow chains
UTMP	Without towing member position
UFFQP	Without second front axle quarter fender mounting position
UCROSSRE	Without cross reinforcement of frame for swap body
U5WLUB	Without fifth wheel lubrication
UTCIND	Without trailer connection indication
HBA-FSFB	Holes for body attachments, flexible/semi-flexible body
HOOK-SC	Snow chain hooks
UPSCAT	Without propeller shaft catcher
UCRANEPK	Without frame-mounted crane interface plates
FBA-BTSF	Front body attachment brackets, lower, for semi-flexible body
RBA-T2	Rear body attachment brackets, lower
HPE-F101	Engine-mounted hydraulic pump F1-101, fixed displacement, single flow
UWHCP	Without wheel chock holder position

List of warnings/errors (2 messages):

	17002	(1) Number of matches for general chassis drawing:0.
	20011	(2) The specification contains unauthorized kola variants for the product type (FM 62 TR): 10500MM, WTD-DUAL, ULHE3

No restrictions violated

Application version: 158, EDB library version: 352.0.2 Elapsed: 2.12 seconds